



University of Tripoli
Faculty of Information Technology



Department of Software Engineering

HTML5 CONCLUSION


SEMANTIC ELEMENTS

Introduction to Internet Programming
ITGS 226 -- S 2023

By: Fatima Ben Lashihar

SEMANTIC ELEMENTS

- <header>
- <nav>
- <section>
- <article>
- <aside>
- <footer>



by: Fatima Ben Lashihar

SEMANTIC ELEMENT: <HEADER>

- The <header> element represents a container for introductory content or a set of navigational links.
- A <header> element typically contains:
 - one or more heading elements (<h1> - <h6>)
 - logo or icon
 - Authorship information
- It is a Block element that may contain block or inline or text content.
- No <footer> or another <header> element as ancestors or descendants

```
<header>
  <h1>Tutorial Republic</h1>
  <nav>
    <p><a href="#">Home</a> |
      <a href="#">About</a> |
      <a href="#">Contact</a> </p>
  </nav>
</header>
```

by: Fatima Ben Lashihar

3

SEMANTIC ELEMEN: <NAV>

- The <nav> element defines a section of navigation links (i.e. links to other pages or to parts within the page itself) in a document.
- It is a Block element that may contain block or inline or text content.

```
<nav>
  <ul>
    <li><a href="#">Home</a></li>
    <li><a href="#">About</a></li>
    <li><a href="#">Contact</a></li>
  </ul>
</nav>
```

by: Fatima Ben Lashihar

4

SEMANTIC ELEMENT: <SECTION>

- The <section> element defines a section in a document.
- Examples of where a <section> element can be used:
 - Chapters
 - Introduction
 - News items
 - Contact information
- A web page could normally be split into sections for introduction, content, and contact information.
- It is a Block element that may contain block or inline or text content.

```
<section>
  <h1>Welcome to Our Website</h1>
  <p>Welcome and thank you. </p>
</section>
```

by: Fatima Ben Lashihar

5

SEMANTIC ELEMENT: <ARTICLE>

- The <article> element specifies independent, self-contained content.
- An article should make sense on its own, and it should be possible to distribute it independently from the rest of the web site.
- Examples of where the <article> element can be used:
 - Forum posts
 - Blog posts
 - User comments
 - Newspaper articles
- It is a Block element that may contain block or inline or text content.

```
<article>
  <h1>Introduction to HTML</h1>
  <p>HTML is a markup language.</p>
</article>
```

by: Fatima Ben Lashihar

6

SEMANTIC ELEMENT: **<ASIDE>**

- The `<aside>` element defines some content aside from the content it is placed in (like a sidebar).
- The `<aside>` content should be indirectly related to the surrounding content.
- It is a Block element that may contain block or inline or text content.

```
<aside>
  <h1>Apollo 13 Facts</h1>
  <p>Apollo 13 was the seventh manned mission in
  the American Apollo space program and the third
  intended to land on the Moon.</p>
</aside>
```

by: Fatima Ben Lashihar

7

SEMANTIC ELEMENT: **<FOOTER>**

- The `<footer>` element defines a footer for a document or section.
- A `<footer>` element typically contains:
 - copyright information
 - contact information
 - back to top links
 - related documents
- You can have several `<footer>` elements in one document.
- It is a Block element that may contain block or inline or text content, but no `<footer>` or `<header>`.

```
<footer>
  <nav>
    <p><a href="#">Terms of Use</a> |
    <a href="#">Privacy Policy</a>
  </nav>
  <p>Copyright © 2014 Tutorial Republic</p>
</footer>
```

by: Fatima Ben Lashihar

8

NON-SEMANTIC ELEMENTS

- <div>
-

by: Fatima Ben Lashihar

(9)

NON-SEMANTIC ELEMENT: <DIV>

- The <div> (short for *division*) tag is generic container for flow content, which has no default rendering or meaning.
- The <div> tag is extensively used to define the structural sections of a document and to layout a web page using CSS.
- It is a Block element that may contain block or inline or text content.

```
<div class="welcome-box">
  <h1>Welcome</h1>
  <p>Hi, welcome to our website.</p>
</div>
```

by: Fatima Ben Lashihar

(10)

NON-SEMANTIC ELEMENT: ****

- The `` tag is generic inline container for phrasing content, which has no default rendering or meaning.
- The `` tag is extensively used to define the structural sections of a document and to layout a web page using CSS.
- It is a Inline element that may contain inline or text content.

```
<p>Here is some  
    <span style="color:red;"> different </span>  
text.</p>
```

```
<p>Read the  
    <span class="important"> Notes </span>  
carefully.</p>
```

by: Fatima Ben Lashihar

(11)

NON-SEMANTIC ELEMENT: ****

- The `` tag is generic inline container for phrasing content, which has no default rendering or meaning.
- The `` tag is extensively used to define the structural sections of a document and to layout a web page using CSS.
- It is a Inline element that may contain inline or text content.

```
<p>Here is some  
    <span style="color:red;"> different </span>  
text.</p>
```

```
<p>Read the  
    <span class="important"> Notes </span>  
carefully.</p>
```

by: Fatima Ben Lashihar

(12)

THE END

by: Fatima Ben Lashihar

(13)